

Aqua-Seal Bronze™

Natural Look Sealer



DESCRIPTION & USE

Aqua-Seal Bronze™ is a water based, natural look, below surface, economical penetrating sealer formulated to provide good stain resistance & excellent water repellancy. Can also be used as a pre-grouting sealer. Breathable - allows excellent Moisture Vapour Transmission (MVT). For indoor, outdoor, domestic & commercial areas where a cost effective sealer is required. NO VOC. **USE:** For stone, tile, grout and other surfaces.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate skin & eye protection & use in a well ventilated area;
3. Surface must be clean, dry & free from any sealers & coatings;
4. Use when surface temperature is between 4°C & 32°C;
5. Do NOT use on underside of tile or stone. If six sided/dip sealing is required, use Ultra-Block™

PRE-GROUT SEALING

1. Allows quick & easy clean-up after grouting as grout may stain surfaces.
2. Do NOT saturate the open grout joints;
3. Allow minimum 24 hours cure time before grouting.
4. Where a dark or contrasting colour is to be used, apply Grout Release Pro™ AFTER a coat of Aqua-Seal Bronze™ or Ultra-Block™ has been applied and has cured.

PREPARATION

Use XtremeClean™ as per label instructions to clean and prepare surface to be sealed.

APPLICATION INSTRUCTIONS:

1. Sweep, vacuum, or wipe surface;
2. Apply to clean, dry surface using a sealer applicator, sealer sponge, roller or paint pad;
3. Work the product thoroughly into the surface using a back-forward motion;
4. For vertical surfaces apply bottom to top & avoid rundown;
5. After 5-10 minutes, wipe the surface COMPLETELY DRY with absorbent paper or cotton towels to remove any excess sealer;
6. DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE;
7. If 2 or more coats are required, allow minimum 30 minutes between coats & follow "Application Instructions" for each coat;
8. 2 hours after the final coat, conduct a test to determine if the surface is properly sealed by applying a few water droplets to the surface. If the water is easily absorbed then apply an additional coat. Wait 2 hours and repeat the test.
9. The surface is ready for light traffic after 2 hours.

LIMITATIONS

- ▶ Sealer will not prevent surface wear or etching from harsh or acidic chemicals
- ▶ Sealer is NOT a waterproofing agent.

EXPECTED WEAR

Will vary depending on texture & hardness of surface, surface wear plus frequency & type of maintenance products used. Harsh cleaning methods, pressure washing, high alkaline, acidic, or solvent-based cleaners or weather exposure will affect wear and performance. Exterior areas may require more frequent applications. **RE-SEAL AS NECESSARY.**

COVERAGE

Full coverage chart at www.aqua-seal.com.au Coverage will vary depending on density, porosity, texture, surface absorption, weather conditions, the application method and number of coats. Approx 40 - 160m² per 4 litre per coat. See table below as a guide:

▶ Basalt / Bluestone Flamed	80 - 100m ²
▶ Encaustic Tiles	60 - 80m ²
▶ Marble Honed	100 - 120m ²
▶ Porcelain Polished	140 - 160m ²
▶ Terracotta Tiles	50 - 70m ²
▶ Travertine Honed	80 - 100m ²

MAINTENANCE

- ▶ EzyClean™ for routine, everyday cleaning;
- ▶ Boost™ for routine cleaning & help prolong sealer life span;
- ▶ XtremeClean™ for periodic heavy duty cleaning;
- ▶ Deep Clean Pro™ for large commercial areas;

HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use
- ▶ Store between 4°C and 32°C.
- ▶ Do not re-use container. Discard in rubbish
- ▶ Clean tools with water.

FIRST AID

Contact a doctor or Poisons Information Centre (Australia 131-126, NZ 0800 764 766). **Skin & Eye Contact:** Irritation is unlikely. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes or until chemical is removed. **Inhalation:** First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. **Ingestion:** If swallowed, do NOT induce vomiting. Wash mouth with water & give some water to drink. **General:** In case of accident or if you feel unwell, seek medical advice immediately.

Code	Size	Barcode Number
140-005	1 litre - Aqua-Seal Bronze	9347177001692
140-006	4 litre- Aqua-Seal Bronze	9347177001708
140-007	20 litre - Aqua-Seal Bronze	9347177001715

PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**