

# Enhance'N'Seal™

## Premium Sealer & Colour Enhancer



### DESCRIPTION & USE

Enhance'N'Seal™ is a 100% actives, premium, below surface, no sheen sealer & colour enhancer formulated to provide maximum stain resistance & also enhance, darken, highlight & rejuvenate colour in porous & unsealed surfaces. Breathable - allows excellent Moisture Vapour Transmission (MVT). LOW VOC's (Volatile Organic Compounds). Non-Flammable. For indoor, outdoor, domestic & commercial applications.

### TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

### PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate skin & eye protection & use in a ventilated area;
3. Surface must be clean & **COMPLETELY** dry & free from any other sealers & coatings;
4. Use when surface temperature is between 4°C & 32°C;
5. Do NOT apply other sealers, coatings or finishes over Enhance'N'Seal™
6. Do NOT use on underside of tile or stone. If underside sealing is required use **Ultra-Block™** only on the underside and sides of the stone. (Do NOT allow **Ultra-Block™** on the top surface if using **Enhance'N'Seal**)
7. Once a surface has been enhanced it **CANNOT** be restored to original look.

### PRE-GROUT SEALING

1. Allows quick & easy clean-up after grouting as grout may stain surfaces.
2. Do NOT saturate the open grout joints;
3. Allow minimum 24 hours cure time before grouting.
4. Where a dark or contrasting colour is to be used, apply **Grout Release Pro™** **AFTER** a coat of **Enhance'N'Seal™** has cured.

### PREPARATION

Use **XtremeClean™** as per label instructions to clean and prepare surface to be sealed.

### APPLICATION INSTRUCTIONS:

1. Sweep, vacuum, or wipe surface;
2. Apply to clean, dry surface using a sealer applicator, sealer sponge, roller or paint pad;
3. Work the product thoroughly into the surface using a back-forward motion;
4. For vertical surfaces apply bottom to top & avoid rundown;
5. After 5-10 minutes, wipe the surface **COMPLETELY DRY** with absorbent paper or cotton towels to remove any excess sealer;
6. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE;**
7. If 2 or more coats are required, allow minimum 30 minutes between coats & follow "Application Instructions" for each coat;
8. 2 hours after the final coat, conduct a test to determine if the surface is properly sealed by applying a few water droplets to the surface. If the water is easily absorbed then apply an additional coat. Wait 2 hours and repeat the test.
9. The surface is ready for light traffic after 2 hours. Keep surface dry for minimum 24 hours. Full cure in 24 hours.

### LIMITATIONS

- ▶ Sealer will not prevent surface wear or etching from harsh or acidic chemicals
- ▶ Sealer is **NOT** a waterproofing agent.

### EXPECTED WEAR

Will vary depending on texture & hardness of surface, surface wear plus frequency & type of maintenance products used. Harsh cleaning methods, pressure washing, high alkaline, acidic, or solvent-based cleaners or weather exposure will affect wear and performance. Exterior areas may require more frequent applications. **RE-SEAL AS NECESSARY.**

### COVERAGE

Full coverage chart at [www.aqua-seal.com.au](http://www.aqua-seal.com.au) Coverage will vary depending on density, porosity, texture, surface absorption, weather conditions, the application method and number of coats. Approx 40 - 160m<sup>2</sup> per 4 litre per coat. See table below as a guide:

▶ Basalt / Bluestone Flamed	100 - 120m <sup>2</sup>
▶ Encaustic Tiles	60 - 80m <sup>2</sup>
▶ Marble Honed	100 - 120m <sup>2</sup>
▶ Sandstone	50 - 70 m <sup>2</sup>
▶ Travertine Honed	80 - 100m <sup>2</sup>

### MAINTENANCE

- ▶ **EzyClean™** for routine, everyday cleaning;
- ▶ **XtremeClean™** for periodic heavy duty cleaning;
- ▶ **Deep Clean Pro™** for large commercial areas;

### HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use
- ▶ Store between 4°C and 32°C.
- ▶ Shelf life is approximately 1 year in un-opened container.
- ▶ Storage beyond that time does not necessarily mean the product is not usable. Do a small test area first.
- ▶ Product may harden or gel in container if not stored correctly or past shelf life. Discard and do not use.
- ▶ Do not re-use container. Discard in rubbish
- ▶ Clean tools with mineral spirits or a solvent before they dry.

### FIRST AID

Contact a doctor or Poisons Information Centre (Aust 131-126, NZ 0800 764 766). Skin & Eye Contact: If in eyes, hold eyelids apart & flush continuously with running water until advised to stop or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing & flush skin or hair with running water. Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water.

Code	Size	Barcode Number
160-003	250ml - Enhance'N'Seal	9347177001296
160-005	1 litre - Enhance'N'Seal	9347177001302
160-006	4 litre - Enhance'N'Seal	9347177001319

### PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**