

Strip-It™

Heavy Duty Sealer & Coating Remover



DESCRIPTION & USE

Strip-It™ is a safer, non-flammable, biodegradable, multi-purpose stripper formulated to stay wet for longer periods to give the product time to break down & help remove most sealers, coatings, epoxy grout haze, urethane coatings, synthetic finishes, adhesives, silicone, paint, heavy wax, deep-set stains and heavy grease build up. **USE:** On all natural stone, ceramic tile, porcelain tile, terracotta and other surfaces.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS & SAFETY DIRECTIONS

1. Read entire label, SDS & technical bulletin before using;
2. Wear appropriate gloves, skin & eye protection and use in a well ventilated area or use an appropriate mask;
3. Use when surface temperature is between 4°C and 32°C.
4. Do **NOT** mix with other chemicals or allow product to come in contact with any non-recommended surfaces;
5. Floor will get slippery during process. Take appropriate precautions to prevent slips or falls;
6. Will affect sealers, coatings, floor finishes & painted surfaces

INSTRUCTIONS:

1. Sweep, vacuum, or wipe surface;
2. Use neat. Do **NOT** dilute;
3. Carefully apply liberal amount of **Strip-It™** to a small manageable area of up to 4m².
4. Spread with a roller, mop, sponge or brush;
5. Allow product to dwell minimum 1 hour without drying or until coating or residue softens.
6. **DO NOT ALLOW PRODUCT TO DRY ON THE SURFACE;**
7. Agitate with solvent resistant scrub pads, scrub brush or scrub machine;
8. Remove the residue with a wet vac or if thick, with clean, absorbent white cotton towels, scoop or shovel;
9. Rinse thoroughly with clean water; (See * Important Note)
10. **REPEAT THE PROCESS AS NECESSARY;**

* IMPORTANT NOTE:

- ▶ Surface ready for light traffic in minimum 1 hour or after all fumes have dissipated.
- ▶ Allow at least 48-hour drying time before applying any sealers, coatings or floor finishes. Always do a test area first before applying to whole area.
- ▶ To help with residue removal, apply **XtremeClean™** diluted 1 part with 5 parts water to the surface after Step 9. Allow dwell time of 5-10 minutes then scrub or agitate. Remove with wet vac then rinse thoroughly. Allow to fully dry.

LIMITATIONS

- ▶ For epoxy grout haze removal, limit dwell time in Step 5 to no more than 30 minutes. Do **NOT** allow puddling in grout joints.
- ▶ Refer to **Aqua-Seal Problem Solver PS04**. Visit our website at www.aqua-seal.com.au
- ▶ Removal of thick coatings may require multiple applications.

COVERAGE

Approx 10-40m² per 4 litre. Coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem & dilution used.

HANDLING, STORAGE & CLEAN UP

- ▶ Close container tightly after each use;
- ▶ Store in original container between 4°C and 32°C;
- ▶ Do not re-use empty container.
- ▶ Discard in rubbish or recycle.
- ▶ Wash tools, gloves & shoes thoroughly with clean water;

FIRST AID

Contact a doctor or Poisons Information Centre (Australia 131-126, NZ 0800 764 766). **Skin & Eye Contact:** If in eyes, hold eyelids apart & flush continuously with running water until advised to stop or for at least 15 minutes. If skin or hair contact occurs, remove contaminated clothing & flush skin or hair with running water. **Inhalation:** If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. **Ingestion:** If swallowed, do **NOT** induce vomiting. Wash mouth with water. **General:** In case of accident or if you feel unwell, seek medical advice immediately.

SAFETY PRECAUTIONS:

- ▶ Avoid contact with skin & eyes.
- ▶ Use a fan or in a well ventilated area.
- ▶ Do **NOT** breath vapours.
- ▶ May cause stomach distress, nausea, vomiting or respiratory tract irritation.

Code	Size	Barcode Number
121-005	1ltr - Strip-It	9347177001401
121-006	4 ltr - Strip-It	9347177001418

PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use. **READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.**