

XtremeClean

Heavy Duty Stone, Tile & Grout Cleaner







DESCRIPTION & USE

XtremeClean[™] is a fast acting concentrated high alkaline cleaner & degreaser. It is designed to remove most dirt, grease, grime, soap scum, wax, oil, mildew, algae, porcelain wax, floor finishes & is ideal for areas that have been neglected or subject to heavy use. USE: On all natural stone, grout, ceramic, porcelain, terracotta, Saltillo, quarry tiles, terrazzo, concrete, pavers & masonry surfaces.

TEST FIRST

Due to the nature of different surfaces, you should do several test areas in inconspicuous areas according to the label instructions to determine surface colour stability and desired results. The end user must determine the suitability of the product for their intended use.

PRECAUTIONS & SAFETY DIRECTIONS

- 1. Always test first;
- 2. Read entire label, SDS & technical bulletin before using;
- 3. Wear appropriate skin & eye protection;
- 4. Use when surface temperature is between 4°C & 32°C;
- 5. Do not mix with other chemicals or allow contact with any non-recommended surfaces;
- 6. Regular use of high alkaline cleaners will affect the performance of sealers, coatings & floor finishes.7. Do NOT use undiluted. The undiluted product can dull or
- discolour some surfaces.

APPLICATION INSTRUCTIONS:

- 1. Sweep, vacuum, or wipe surface;
- 2. Dilute XtremeClean™ as follows depending on the severity of the problem:
 - a) LIGHT: Dilute 1 part XtremeClean™ to 15 parts clean
 - b) MODERATE: Dilute 1 part XtremeClean[™] to 10 parts
 - c) HEAVY: Dilute 1 part XtremeClean[™] to 5 parts clean
 - d) STRIPPING: Dilute 1 part XtremeClean™ to 3 parts clean water;
- 3. Carefully apply the solution to surface with a sponge or
- 4. Allow minimum dwell time of 10 minutes. Longer
- dwell time may be required.

 5. DO NOT ALLOW THE PRODUCT TO DRY ON THE SURFACE
- Scrub with a white nylon pad, scrub brush or scrub machine;
- Remove the dirty solution with a wet vac or mop;
- 8. Rinse thoroughly with clean water;9. Repeat the process as necessary.

Note 1: Heavily soiled areas may require longer dwell time and/or stronger solution.

Note 2: Add MicroScrub™ to standing solution just prior to scrubbing to boost performance where required.

LIMITATIONS

- Badly stained grout may require re-colouring with Renue'N'Seal™ or re-grouting.
- May lighten some dark grouts & affect some grout colourants.

COVERAGE

The coverage will vary depending on density, porosity, texture, surface absorption, weather, time solution left on surface, the application method, severity of the problem and dilution used.

HANDLING, STORAGE & CLEAN UP

- Close container tightly after each use; Store between 4°C and 32°C.
- Do not re-use container. Discard in rubbish.

► Clean tools and hands with clean water.

FIRST AID

Contact a doctor or Poisons Information Centre (Australia Ph: 131-126, NZ Ph: 0800 764766). Ingestion: Do not induce yomiting. Give water or milk to drink. Eyes: Immediately flush eyes with clean, running water for at least 15 minutes & see a doctor. Skin & Hair: Remove contaminated clothing. Immediately wash contaminated skin & hair with plenty of water. Inhalation: Remove victim from exposure, to fresh air. Seek medical advice. General: If irritation persists or feeling unwell, seek medical attention.

SAFETY PRECAUTIONS

- Avoid contact with skin & eyes;
- Wear protective glasses and gloves when mixing or
- Do NOT kneel in this product. Avoid all skin contact..

Code	Size	Barcode Number
103-005	1 litre - XtremeClean	9347177000060
103-006	4 litre - XtremeClean	9347177000077

PRODUCT WARRANTY

PRODUCT WARRANTY

Aqua-Seal STS™ "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The ord user must determine the suit belief to the required the printed user. implied. The end user must determine the suitability of the product for their intended use. READ ENTIRE LABEL & ALWAYS DO A TEST FIRST.



